

FEATURES

ECO SEEDER

All Eco Seeders come with the following features as standard equipment:

- 25mm coil tines: strong and maintain their shape for more accurate seeding
- Duncan 'T' Boot: creates an excellent seed bed environment
- NI-Hard cast points: exceptional wear in all conditions

- Tungsten tile on the leading edge to increase the life of the point. (Tungsten chip points also available for stony conditions)
- Weigh kit
- Rear foot board

Optional Equipment:

- Disc openers on the front of the drill
- Hectare meter
- Trailing kit to convert from 3PL
- 3Pl kit to convert from trailing

DIMENSIONS & CAPACITIES

16/18 ROW ECO SEEDER	Single Box Trailing		Dual Box Trailing		Single Box 3PL		Dual Box 3PL	
	16	18	16	18	16	18	16	18
Number of runs	16	18	16	18	16	18	16	18
Sowing width (mm)	2376	2673	2376	2673	2376	2673	2376	2673
Width - overall (mm)	2995	2995	2995	2995	2995	2995	2995	2995
Height - GWU (mm)	1623	1623	1623	1623	1623	1623	1623	1623
Row spacing (mm)	148.5	148.5	148.5	148.5	148.5	148.5	148.5	148.5
Weight - incl discs (Kg)	1050	1130	1150	1256	998	1078	1098	1204
Box capacity (L)	338	338	326ea	326ea	338	338	326ea	326ea
Length (mm)	2720	2856	2870					

14 ROW ECO SEEDER	Single Box 3PL
Sowing width (mm)	2079
Width - overall (mm)	2698
Height - GWU (mm)	1623
Row spacing (mm)	148.5
Weight - incl discs (Kg)	731
Box capacity (L)	295
Length (mm)	1685

DUNCAN AG NEW ZEALAND  
PO BOX 2018,  
WASHDYKE 7941, TIMARU  
PH: 0800 177 171  
Email: admin@duncanag.co.nz  
www.duncanag.com


DUNCAN AG AUSTRALIA  
4B SILVERTON CLOSE,  
NORTH LAVERTON, VICTORIA 3026  
PH: 0061 393 149 666  
Email: admin@duncanag.com.au

Appointed Duncan Dealer




In accordance with the company's policy of continuous improvement to its machines, alterations in specifications may be made without notice. The company accepts no responsibility for any discrepancies which may occur between specifications of its machines and the descriptions thereof contained in this publication.





NEW design box giving better seed flow



NEW design agitator shaft to help prevent seed compaction




NEW optional following tools: Uni-Roller and/or Tine Harrows



Duncan 'T' boots have extra strength with Ni-hard steel and a tungsten tile on the leading edge


Proven 25mm coil tines for superior strength and consistent seeding



Front disc openers are available as an option




Peg roller seeder unit for sowing a wide range of products




This weigh kit including scales comes as standard

The bin lids open to a full 90° degrees




Drive to the gearbox is taken from the ground wheel via the smaller sprung jockey wheel



Easy to access rear footboard is standard



Easy to adjust gearbox with excellent sowing range



Dual Box 18 Row



Single Box 14 Row

